

Battery powered plastic strapping tool for demanding applications



Characteristics

| | |
|-------------------------|--|
| Strapping qualities: | Polyester (PET) and Polypropylene (PP) plain and embossed |
| Strapping dimensions: | width 16.0 – 19.0 mm / 5/8 – 3/4" thickness 0.65 – 1.35 mm / .026 – .053" |
| Weight incl. battery: | 4.3 kg / 9.6 lbs |
| Tool size with battery: | L351 x W134 x H143 mm / 13.8" x 5.3" x 5.6" |
| Type of seal: | Friction weld sealing |
| Average seal strength: | approx. 75% (dependent on strap quality) |
| Tension force: | 500 – 4000 N / 112 – 900 lbs (adjustable) |
| Tension speed: | 49 – 79 mm/s / 1.9 – 3.1 inch/s |
| Power supply: | Battery Li-Ion 18VDC / 4.0 Ah |
| Suspension bracket: | optional |

Advantages

- High tension force up to 4000N / 900 lbs
- Tension force and sealing time adjustable with simple knobs
- Tool in both semi-automatic and automatic (single button) version available for efficient operation
- Brushless motor for less maintenance and improved life time
- Improved plates and guides – less effort to remove the tool from the strap
- No tension rocker – easier to remove tool from small package surfaces
- Motor temperature monitoring to protect motor from overheating
- Cycle counter included (special reader required)
- Battery well protected
- Battery charge indicator included
- Simple one-handed operation
- Tool is fully covered for finger protection
- Optional motor cooling fan available to reduce overheating risk



Datasheet P329

Battery powered manual plastic strapping tool

Chart of types model P329

| Item no. | Model | Strap widths | | Strap thicknesses | | Max. tension | | Tension speed | |
|----------|-------------------|--------------|------|-------------------|-----------|--------------|-----|---------------|-----------|
| | | mm | inch | mm | inch | N | lbs | mm/sec. | inch/sec. |
| 43.2522 | P329/16/0.65-1.05 | 16 | 5/8 | 0.65-1.05 | .026-.041 | 4000 | 900 | 49-79 | 1.9-3.1 |
| 43.2533 | P329/19/1.06-1.35 | 19 | 3/4 | 1.06-1.35 | .042-.053 | 4000 | 900 | 49-79 | 1.9-3.1 |

Battery chargers for model P329

| Item no. | Model | Voltage / frequency | Countries |
|----------|------------------------|---------------------|--|
| N5.4447 | Li-Ion battery charger | 120 V / 50-60 Hz | BR, C, CDN, CO, CR, DOM, EC, GCA, J, JA, KSA, LB, MEX, NIC, PA, Puerto Rico, RC, RP, USA, YV |

Battery for model P329

| Item no. | Battery | Voltage | Capacity | Charging time |
|----------|-------------|---------|----------|-----------------|
| N5.4349 | Accu Li-Ion | 18VDC | 4.0 Ah | approx. 80 min. |

Accessories

| | |
|----------|--|
| P32.0223 | Suspension bracket (pivoted) |
| P32.0231 | Suspension bracket (fixed) |
| P32.0224 | Wearing plate (metal) for rough and hard surfaces |
| P32.0225 | Protection plate (metal) to protect complete bottom side |
| P32.0228 | Motor cooling fan |
| P32.2061 | Turning button kit |