

# | PALLET<sup>3</sup> |

## PALLET LABELING



---

### PALLET LABELING

Pallet labeling systems are able to cover any application that requires to printing and apply pressure-sensitive A5 logistic labels on different sides of a pallet (up to 3) according to GS1 standards.

# | PALLET<sup>3</sup> |

## PALLET LABELING



### KEY FEATURES

- Compliant with DIN EN 415 standards
- Intrinsically safe: NO need for protective barriers
- The aluminum cabinet protects the system from the external environment
- Ideal solution to print and apply A5 logistic labels on up to 3 adjacent sides of a pallet

---

End-of-line 3 side Print&Apply out of the box with a multi-axis, fully programmable, electric movements for a freely configurable and precise label positioning. With advanced, built-in safety features, can be installed without safety barriers.

### GENERAL FEATURES

Label position	Front + Side + Back
Label size	Typically 160x220 mm (6.3x8.6 inches)
Label roll diameter	Internal 76 mm (3 inches), external up to 350 mm (14 inches)
Application technology	Fully enclosed, with automatic door opening for the applicator
Applicator group motion	Landscape/Portrait label orientation, Barcode reader to check code readability

# | PALLET<sup>3</sup> |

## PALLET LABELING



---

### **Pallet<sup>3</sup>**

#### HYBRID 3-SIDE APPLICATOR FOR PALLET

- Programmable multi-axis linear applicator with electric motion
- Smart variable distance positioning of the actuator
- Tamp-Blow technology for maximum labeling flexibility
- Rotary tamp for portrait/landscape label orientation



Front, top  
and lateral side